

INDIA KA WIN WIN TRACTOR



VST 9045 DI+



**PNEUMATIC ASSISTED
FRONT OPENING HOOD**



**BOW TYPE
FRONT AXLE**



**HEAVY DUTY
HITCH RAIL**



**DRY TYPE
AIR CLEANER**



**ROBUST
REAR AXLE**



**1800 KG
LIFT CAPACITY**



**OIL IMMERSED
BRAKE**



**8+2 HEAVY DUTY
TRANSMISSION**



**DUAL DIAPHRAGM
CLUTCH**

Crops

TECHNICAL SPECIFICATION

Key Applications



MILLETS



COTTON



MAIZE



SUGARCANE



SUNFLOWER

AGGREGATES	PARAMETERS	VST 9045 DI ⁺
ENGINE	ENGINE TYPE	TREM IIIA, NATURALLY ASPIRATED DI ENGINE
	HP CATEGORY (kW)	45 (33.55)
	NO. OF CYLINDERS	3
	RATED ENGINE SPEED	2000
	DISPLACEMENT (cc)	3120
	COOLING	WATER COOLED
	AIR CLEANER	DRY TYPE
TRANSMISSION	TORQUE Kgm (nm)	17.85 (175)
	GEAR BOX TYPE	SLIDING MESH
	NO. OF GEARS	8F + 2R
	SHIFTING PATTERN	CENTER SHIFT
	CLUTCH TYPE	DUAL DIAPHRAGM CLUTCH
	SPEED FORWARD (km/hr)	2.21 - 30.96
	SPEED REVERSE (km/hr)	2.76 - 10.89
	PEDAL TYPE	PUSH TYPE
	BRAKES	OIL IMMERSED DISC BRAKES
	NO. OF DISCS ON EACH WHEEL SIDE	4
	STEERING	MANUAL/POWER *
	PTO	GSPTO
	PTO (MAXIMUM) SPEED	540
POWER DRIVE	2WD	
FUEL TANK	CAPACITY (L)	50
HYDRAULIC	ADDC	AUTOMATIC DRAFT AND DEPTH CONTROL (ADDC)
	LIFTING CAPACITY (kg)	1800
TYRES SIZE	FRONT	6.0 X 16
	REAR	13.6 X 28
	OVERALL LENGTH (mm)	3070
DIMENSIONS & CAPACITY	OVERALL WIDTH (mm)	1740
	OVERALL HEIGHT (mm)	1980
	WHEEL BASE (mm)	2020
	GROUND CLEARANCE (mm)	430
	TURNING RADIUS (m)	2.80
	TOTAL WEIGHT (kg)	1880



MB PLOUGH



DUCK FOOT



ROTOVATOR



HAULAGE



DOZER

*OPTIONAL



Trust of >7 lakh farmers, Legacy of >50 years



Widest working range (17 HP to 50 HP)



No.1 Power Tiller brand



1st 4WD compact Tractors



Global footprints in > 40 countries



Year on Year Growth Rate of over 20%



VST TILLERS TRACTORS LTD.

Regd. Office: Plot No- 1, Dyavasandra Indl. Layout, Whitefield Road, Mahadevapura Post, Bengaluru-560048, Karnataka, INDIA
Phone: +91-80-67141111, e-mail: info@vsttractors.com, CIN: L34101KA1967PLC001706. www.vsttractors.com

Disclaimer: Pictures used here are for illustration purpose only. Product specifications are subject to change without prior notice. Performance of the machine may vary with user/field/working conditions

Authorised Dealer

